



Totem 20

2 MILLION BTU INDIRECT HEATER



OPERATING SPECIFICATIONS:

- 2 million BTU (2,000,000)
- 30 hour continuous run time
- 15 GPH max fuel consumption— 450 gallon fuel capacity
- 100% spill containment

HEATER SYSTEM:

- Indirect fired for clean air
- 3—20" duct outlets
- Hi / Lo burner settings
- 170° temp rise
- Beckett burner
- VFD (variable frequency drive) protected 10,000 cfm blower
- Dual pass heat exchanger for optimal efficiency
- Optional stainless steel combustion chamber and heat exchanger

GENERATOR:

- Perkins liquid cooled diesel engine
- 20 kW continuous duty power rating
- Safety shutdowns on engine
- Easy service access

WEIGHTS AND DEMINIONS:

Overall Height (without exhaust)	97 inches
Overall Length (with tongue)	292 inches
Overall Width (widest point)	91 inches
Weight (operating)	11,500 lbs
Weight (shipping)	8,300 lbs

Totem Equipment & Supply Inc.

2536 Commercial Drive Anchorage, Alaska 99501
(907) 276-2858 Phone (907) 258-4623 Fax

E-mail: sales@toteminc.com

On The Web: www.toteminc.com