


heat wagon



342 N. Co. Rd. 400 East
Valparaiso, IN 46383

219-464-8818 • 888-432-8924 • Fax 800-255-7985

Model S1505

SPECIFICATIONS

Input	1,500,000 BTU/Hi Fire	
	800,000 BTU/Lo Fire	
Fuel	Vapor Propane	
	Natural Gas	
Inlet Pressure	Max W.C.	Min W.C.*
Propane	14" w.c.	9" w.c.
Natural Gas	14" w.c.	9" w.c.
Manifold Pressure	Propane	2.7" w.c.
	Natural Gas	7.2" w.c.
Gas Consumption	16.4	GPH LP
	1500	CFH NG
Gas Connection	1 1/4" NPT	
Electrical Requirements	120 Volts	20 amp circuit
Fan	7000 CFM	1 HP
Thermostat	HI - LO	
Temp Rise	350°F	
Shipping Dimensions	69"L x 32"W x 41.5"H	
Approximate Weight	300 lbs.	

*For lower pressures consult authorized Heat Wagon distributor or the factory.



Propane & Natural Gas
Portable Space Heater

Features

- AGA Certified
- Air flow switch
- Burner heat shield
- Dual fuel
- Flame safeguard control

- Hi limit switch
- Motor overload - manual reset
- Panel mounted thermostat
- Panel mounted voltage meter
- Stackable design
- Weather sealed control box
- 6" wheels, carrying bars & lifting loop

Benefits

- Tested to ANSI standard Z83.7 (1990)
- Safe fuel shutdown if combustion air is interrupted
- Low housing temperature
- Simple lever change from propane to natural gas
- Safe monitoring of combustion, one trial electronic ignition with 4.7 second shutdown
- Protects heater by shutting down if unit is being overfired
- Protects heater by shutting down if voltage is too low
- Automatically cycles the heater hi/lo
- Easy monitoring of supply voltage to ensure trouble-free operation
- Less need for large storage space
- Indoor/outdoor usage
- Easy relocation by one person

www.heatwagon.com